



#### Main

Range	Prisma
Range of product	Prisma P
Product or component type	Connection transfer assembly
Product name	Prisma P enclosure
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Complementary

Cubicle-device connection	Connection transfer assembly
Poles description	4P
Installation description	Cubicle - width 650 mm
Installed device	<p>EasyPact: fixed CVS400 without earth leakage protection - control: toggle horizontal installation</p> <p>EasyPact: fixed CVS630 without earth leakage protection - control: toggle horizontal installation</p> <p>ComPact: fixed NSX400 with earth leakage protection - control: toggle horizontal installation</p> <p>ComPact: fixed NSX630 with earth leakage protection - control: toggle horizontal installation</p> <p>ComPact: plug-in NSX400 without earth leakage protection - control: toggle horizontal installation</p> <p>ComPact: plug-in NSX630 without earth leakage protection - control: toggle horizontal installation</p> <p>ComPact: drawout NSX400 without earth leakage protection - control: toggle horizontal installation</p> <p>ComPact: drawout NSX630 without earth leakage protection - control: toggle horizontal installation</p> <p>ComPact: plug-in NSX400 with earth leakage protection - control: toggle horizontal installation</p> <p>ComPact: plug-in NSX630 with earth leakage protection - control: toggle horizontal installation</p> <p>ComPact: drawout NSX400 with earth leakage protection - control: toggle horizontal installation</p> <p>ComPact: drawout NSX630 with earth leakage protection - control: toggle horizontal installation</p> <p>EasyPact: fixed CVS400 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>EasyPact: fixed CVS630 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: fixed NSX400 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: fixed NSX400 without earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: plug-in NSX400 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: plug-in NSX400 without earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: drawout NSX400 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: drawout NSX400 without earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: fixed NSX630 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: fixed NSX630 without earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: plug-in NSX630 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: plug-in NSX630 without earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: drawout NSX630 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: drawout NSX630 without earth leakage protection - control: motor mechanism horizontal installation</p> <p>EasyPact: fixed CVS400 with earth leakage protection - control: toggle horizontal installation</p> <p>EasyPact: fixed CVS400 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>EasyPact: fixed CVS630 with earth leakage protection - control: toggle horizontal installation</p> <p>EasyPact: fixed CVS630 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: fixed NSX400 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: fixed NSX400 with earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: plug-in NSX400 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: plug-in NSX400 with earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: drawout NSX400 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: drawout NSX400 with earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: fixed NSX630 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: fixed NSX630 with earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: plug-in NSX630 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: plug-in NSX630 with earth leakage protection - control: motor mechanism horizontal installation</p>

[I <sub>e</sub> ] rated operational current	630 A
[I <sub>n</sub> ] rated current	630 A
Busbar cross section	32 x 6 mm
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Smooth Matt
Height	250 mm
Net weight	3.82 kg





## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.78 kg
Package 1 Height	16 cm
Package 1 width	27.6 cm
Package 1 Length	39.8 cm
Unit Type of Package 2	P12
Number of Units in Package 2	27
Package 2 Weight	114.1 kg
Package 2 Height	61 cm
Package 2 width	80 cm
Package 2 Length	120 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>