



Main

Range	Prisma
Range of product	Prisma P
Product or component type	Connection
Product name	Prisma P enclosure
Accessory / separate part category	Connection accessory
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Complementary

Cubicle-device connection	Linergy busbar
Poles description	3P
Installation description	Cubicle - width 650 mm
Installed device	ComPact: plug-in NSX400 without earth leakage protection - control: toggle horizontal installation ComPact: plug-in NSX630 without earth leakage protection - control: toggle horizontal installation ComPact: drawout NSX400 without earth leakage protection - control: toggle horizontal installation ComPact: drawout NSX630 without earth leakage protection - control: toggle horizontal installation ComPact: plug-in NSX400 with earth leakage protection - control: toggle horizontal installation ComPact: plug-in NSX630 with earth leakage protection - control: toggle horizontal installation ComPact: drawout NSX400 with earth leakage protection - control: toggle horizontal installation ComPact: drawout NSX630 with earth leakage protection - control: toggle horizontal installation
[Ie] rated operational current	630 A
[In] rated current	630 A
Busbar cross section	30 x 10 mm
Net weight	4 kg
Quantity per set	Set of 1
Functional unit	650 mm 400 mm Prisma P cubicle ComPact NSX400 without plug-in toggle horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX400 without drawout toggle horizontal 3P 1 direct 6 650 mm 400 mm Prisma P cubicle ComPact NSX630 without plug-in toggle horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX630 without drawout toggle horizontal 3P 1 direct 6 650 mm 400 mm Prisma P cubicle ComPact NSX400 with plug-in toggle horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX400 with drawout toggle horizontal 3P 1 direct 6 650 mm 400 mm Prisma P cubicle ComPact NSX630 with plug-in toggle horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX630 with drawout toggle horizontal 3P 1 direct 6

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	4 kg
Package 1 Height	12 cm
Package 1 width	21 cm
Package 1 Length	30.5 cm
Unit Type of Package 2	P12
Number of Units in Package 2	70
Package 2 Weight	280 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free plastic parts product