04489

Connection Fixed MTZ1/NT 3P 1600A Prisma P

Green Premium™ Product

Main

Range	Prisma
Range of product	Prisma P
Product or component type	Connection
Product name	Prisma P enclosure
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Complementary

Cubicle-device connection	Linergy busbar
Poles description	3P
Installation description	Cubicle - width 650 mm
Cubicle depth	400 mm: front 400 + 400 mm: rear
Installed device	Masterpact: fixed NT16 - control: toggle vertical installation Masterpact: fixed NT16 - control: motor mechanism vertical installation
[Ie] rated operational current	1600 A
[In] rated current	1600 A
Busbar cross section	80 x 10 mm
Height	150 mm
Width	550 mm
Depth	300 mm
Net weight	14.56 kg
Quantity per set	Set of 1
Functional unit	650 mm 400 mm Prisma P cubicle Masterpact NT16 fixed toggle vertical 3P 1 front connection on adaptor 14 650 mm 400 mm Prisma P cubicle Masterpact NT16 fixed motor mechanism vertical 3P 1 front connection on adaptor 14 650 mm 800 mm Prisma P cubicle Masterpact NT16 fixed toggle vertical 3P 1 rear connection on adaptor 11 650 mm 800 mm Prisma P cubicle Masterpact NT16 fixed motor mechanism vertical 3P 1 rear connection on adaptor 11 650 mm 800 mm Prisma P cubicle Masterpact NT16 fixed toggle vertical 3P 1 rear connection on Canalis 16 650 mm 800 mm Prisma P cubicle Masterpact NT16 fixed motor mechanism vertical 3P 1 rear connection on Canalis 16

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	14.56 kg
Package 1 Height	11 cm
Package 1 width	12 cm
Package 1 Length	54 cm
Unit Type of Package 2	P12
Number of Units in Package 2	28

Package 2 Weight	407.68 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free plastic parts product

Life Is On | Schneider Electric