



Main

Range	Prisma
Range of product	Prisma P
Product or component type	Connection
Product name	Prisma P enclosure
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Complementary

Cubicle-device connection	Linery busbar
Poles description	4P
Installation description	Cubicle - width 650 mm
Cubicle depth	400 mm: front 400 + 400 mm: rear
Installed device	ComPact: drawout NS1600 - control: direct front rotary handle vertical installation ComPact: drawout NS1600 - control: motor mechanism vertical installation ComPact: drawout NS1600 - control: toggle vertical installation Masterpact: drawout NT16 - control: toggle vertical installation Masterpact: drawout NT16 - control: motor mechanism vertical installation
[Ie] rated operational current	1600 A
[In] rated current	1600 A
Busbar cross section	80 x 10 mm
Height	150 mm
Width	550 mm
Depth	300 mm
Net weight	21.72 kg
Quantity per set	Set of 1
Functional unit	650 mm 800 mm Prisma P cubicle ComPact NS1600 drawout toggle vertical 4P 1 rear connection on Canalis 16 650 mm 800 mm Prisma P cubicle ComPact NS1600 drawout direct front rotary handle vertical 4P 1 rear connection on Canalis 16 650 mm 800 mm Prisma P cubicle ComPact NS1600 drawout motor mechanism vertical 4P 1 rear connection on Canalis 16 650 mm 400 mm Prisma P cubicle ComPact NS1600 drawout toggle vertical 4P 1 front connection on adaptor 15 650 mm 400 mm Prisma P cubicle ComPact NS1600 drawout direct front rotary handle vertical 4P 1 front connection on adaptor 15 650 mm 400 mm Prisma P cubicle ComPact NS1600 drawout motor mechanism vertical 4P 1 front connection on adaptor 15 650 mm 400 mm Prisma P cubicle Masterpact NT16 drawout toggle vertical 4P 1 front connection on adaptor 15 650 mm 400 mm Prisma P cubicle Masterpact NT16 drawout motor mechanism vertical 4P 1 front connection on adaptor 15 650 mm 800 mm Prisma P cubicle Masterpact NT16 drawout toggle vertical 4P 1 rear connection on adaptor 11 650 mm 800 mm Prisma P cubicle Masterpact NT16 drawout motor mechanism vertical 4P 1 rear connection on adaptor 11 650 mm 800 mm Prisma P cubicle Masterpact NT16 drawout toggle vertical 4P 1 rear connection on Canalis 16 650 mm 800 mm Prisma P cubicle Masterpact NT16 drawout motor mechanism vertical 4P 1 rear connection on Canalis 16

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	21.72 kg
Package 1 Height	11 cm
Package 1 width	12.5 cm
Package 1 Length	53.5 cm
Unit Type of Package 2	P12
Number of Units in Package 2	14
Package 2 Weight	304.08 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free plastic parts product