




Main

Range	Prisma
Range of product	Prisma P
Product or component type	Interface and connection Canalis
Product name	Prisma P enclosure
Accessory / separate part category	Interface accessory
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Complementary

Cubicle-device connection	KT with Canalis
Poles description	4P
Installation description	Cubicle - width 650 mm
Cubicle depth	600 mm: front 600 + 400 mm: rear
Installed device	Masterpact: drawout NW08...16 - control: toggle vertical installation Masterpact: fixed NW08...16 - control: toggle vertical installation
[I _e] rated operational current	1600 A
[I _n] rated current	1600 A
Colour	Stainless steel
Height	350 mm
Width	575 mm
Depth	420 mm
Net weight	49.9 kg
Quantity per set	Set of 1
Functional unit	650 mm 600 mm Prisma P cubicle Masterpact NW08...16 drawout toggle vertical 4P 1 front connection on Canalis 27 650 mm 1000 mm Prisma P cubicle Masterpact NW08...16 drawout toggle vertical 4P 1 rear connection on Canalis 17 650 mm 600 mm Prisma P cubicle Masterpact NW08...16 fixed toggle vertical 4P 1 front connection on Canalis 27 650 mm 1000 mm Prisma P cubicle Masterpact NW08...16 fixed toggle vertical 4P 1 rear connection on Canalis 16

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	49.9 kg
Package 1 Height	60 cm
Package 1 width	60 cm
Package 1 Length	80 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information