

Product data sheet

Characteristics

04738

CANALIS Connection 4000A MTZ2/NW 4P

Prisma P



Main

Range	Prisma
Range of product	Prisma P
Product or component type	Interface and connection Canalis
Product name	Prisma P enclosure Canalis KT busbar trunking Masterpact NW circuit breaker
Accessory / separate part category	Interface accessory
Standards	IEC 61439-2, inside enclosure IEC 61439-1, inside enclosure
Product certifications	ASEFA KEMA

Complementary

Cubicle-device connection	KT with Canalis
Poles description	4P
Location of connection	Upstream
Installation description	Cubicle 4000A - width 650 mm
Cubicle depth	600 + 400 mm: rear
Installed device	Masterpact: NW40 vertical installation - rear connection
[Ie] rated operational current	4000 A
Material	Metal
Height	350 mm
Width	575 mm
Depth	450 mm
Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	88.2 kg
Package 1 Height	56.5 cm
Package 1 width	60 cm
Package 1 Length	80 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
Circularity Profile	<input checked="" type="checkbox"/> End Of Life Information