



**Main**

Range	Prisma
Range of product	Prisma G Prisma P
Product or component type	Insulated flexible bar
Product name	Prisma G enclosure Prisma P enclosure Prisma iPM L enclosure Prisma iPM M enclosure
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

**Complementary**

Installation description	Cubicle Floor-standing enclosure Wall-mounted enclosure
[Ie] rated operational current	250 A
[In] rated current	250 A
Busbar cross section	20 x 3 mm
Length	1800 mm
Net weight	1.68 kg
Quantity per set	Set of 1

**Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.68 kg
Package 1 Height	2 cm
Package 1 width	9 cm
Package 1 Length	192 cm
Unit Type of Package 2	P2M
Number of Units in Package 2	130
Package 2 Weight	218.4 kg
Package 2 Height	36 cm
Package 2 width	120 cm
Package 2 Length	200 cm

**Offer Sustainability**

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes

---

RoHS exemption information

Yes

China RoHS Regulation

China RoHS Declaration

Environmental Disclosure

Product Environmental Profile

---