



Main

Range	Prisma
Range of product	Prisma G Prisma P
Product or component type	Insulated flexible bar
Product name	Prisma G enclosure Prisma P enclosure Prisma iPM L enclosure Prisma iPM M enclosure
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Complementary

Installation description	Cubicle Floor-standing enclosure Wall-mounted enclosure
[Ie] rated operational current	520 A
[In] rated current	520 A
Busbar cross section	32 x 5 mm
Length	1800 mm
Net weight	3.38 kg
Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.25 kg
Package 1 Height	2 cm
Package 1 width	11 cm
Package 1 Length	192 cm
Unit Type of Package 2	P2M
Number of Units in Package 2	100
Package 2 Weight	338 kg
Package 2 Height	39 cm
Package 2 width	120 cm
Package 2 Length	200 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information

Yes

China RoHS Regulation

China RoHS Declaration

Environmental Disclosure

Product Environmental Profile
