

Main

Range	Prisma
Range of product	Prisma G Prisma P
Product or component type	Insulated flexible bar
Product name	Prisma G enclosure Prisma P enclosure
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA




Complementary

Installation description	Cubicle Floor-standing enclosure Wall-mounted enclosure
[Ie] rated operational current	580 A
[In] rated current	580 A
Busbar cross section	32 x 6 mm
Length	1800 mm
Net weight	3.88 kg
Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.75 kg
Package 1 Height	2 cm
Package 1 width	11 cm
Package 1 Length	192 cm
Unit Type of Package 2	P2M
Number of Units in Package 2	100
Package 2 Weight	388 kg
Package 2 Height	35 cm
Package 2 width	120 cm
Package 2 Length	200 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation

 [China RoHS Declaration](#)

Environmental Disclosure

 [Product Environmental Profile](#)
