



**Main**

Range	Linergy
Range of product	Linergy
Product or component type	Copper busbar
Product name	Linergy BS
Range compatibility	Prisma G enclosure Prisma P enclosure
Busbar description	Flat bar
Quantity per set	Set of 4

**Complementary**

Installation direction	Vertical, operating position: rear
Installation description	Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing enclosure - width 300 mm Wall-mounted enclosure - width 300 mm
[Ui] rated insulation voltage	1000 V
[Ie] rated operational current	160 A
[Ipk] rated peak withstand current	30 kA
Busbar cross section	15 x 5 mm
Length	1000 mm
Net weight	2.68 kg
Type of busbar connection	M6 threaded hole
Connection pitch	Connection each 25 mm
Support thickness	5 mm

**Environment**

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASEFA

**Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.68 kg
Package 1 Height	2 cm
Package 1 width	13 cm
Package 1 Length	110 cm
Unit Type of Package 2	P12
Number of Units in Package 2	60
Package 2 Weight	160.8 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	120 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product