



### Main

Range	Linergy
Range of product	Linergy
Product or component type	Copper busbar
Product name	Linergy BS
Range compatibility	Prisma G enclosure Prisma P enclosure
Busbar description	Flat bar
Quantity per set	Set of 4

### Complementary

Installation direction	Vertical, operating position: rear
Installation description	Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
[Ui] rated insulation voltage	1000 V
[Ie] rated operational current	250 A
[Ipk] rated peak withstand current	40 kA
I <sup>2</sup> t on activation	169000 kA <sup>2</sup> .s
Busbar cross section	20 x 5 mm
Length	1400 mm
Net weight	4.94 kg
Type of busbar connection	M6 threaded hole
Connection pitch	Connection each 25 mm
Support thickness	5 mm

### Environment

Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	4.94 kg
Package 1 Height	2.2 cm
Package 1 width	13 cm
Package 1 Length	150 cm
Unit Type of Package 2	P2M
Number of Units in Package 2	56
Package 2 Weight	286.96 kg
Package 2 Height	21 cm
Package 2 width	120 cm
Package 2 Length	200 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product