



Main

Range	Linergy
Range of product	Linergy
Product or component type	Copper busbar
Product name	Linergy BS
Range compatibility	Prisma G enclosure Prisma P enclosure
Busbar description	Flat bar
Quantity per set	Set of 4

Complementary

Installation direction	Vertical, operating position: rear
Installation description	Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
[Ui] rated insulation voltage	1000 V
[Ie] rated operational current	400 A
[Ipk] rated peak withstand current	55 kA
I ² t on activation	625000 kA ² .s
Busbar cross section	32 x 5 mm
Length	1400 mm
Net weight	8 kg
Type of busbar connection	M6 threaded hole
Connection pitch	Connection each 25 mm
Support thickness	5 mm

Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASEFA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	8 kg
Package 1 Height	2.2 cm
Package 1 width	15 cm
Package 1 Length	152 cm
Unit Type of Package 2	P2M
Number of Units in Package 2	56
Package 2 Weight	448 kg
Package 2 Height	21 cm
Package 2 width	120 cm
Package 2 Length	200 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product