



Main

Range	Linergy
Range of product	Linergy
Product or component type	PE conductor flat bar
Product name	Linergy TB
Range compatibility	Prisma P enclosure
Accessory / separate part category	Earthing accessory
Quantity per set	Set of 1

Complementary

Installation direction	Horizontal Vertical
Installation description	Cubicle
[Ie] rated operational current	600 A
[Icw] rated short-time withstand current	40 KA (1 s) for 3 supports (vertical position) 40 kA (1 s) (horizontal position)
Busbar cross section	50 x 5 mm
Length	1675 mm
Net weight	3.64 kg
Type of busbar connection	Ø 10 mm drilled hole
Support thickness	5 mm

Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASEFA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.55 kg
Package 1 Height	2 cm
Package 1 width	12 cm
Package 1 Length	183 cm
Unit Type of Package 2	P2M
Number of Units in Package 2	100
Package 2 Weight	364 kg
Package 2 Height	34 cm
Package 2 width	120 cm
Package 2 Length	200 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product