



Main

Range	Linergy
Range of product	Linergy
Product or component type	Copper busbar
Product name	Linergy BS
Range compatibility	Prisma P enclosure
Busbar description	Flat bar
Quantity per set	Set of 1

Complementary

Installation direction	Vertical, operating position: lateral Horizontal, operating position: top Horizontal, operating position: bottom
Installation description	Cubicle - width 650 mm Cubicle - width 650 + 150 mm Cubicle duct - width 300 mm Cubicle duct - width 400 mm
[I _e] rated operational current	1880 A at 35 °C
[I _{cw}] rated short-time withstand current	60 KA (1 s) for 2 supports (horizontal position) 85 KA (1 s) for 3 supports (horizontal position) 40 KA (1 s) (horizontal position) 85 KA (1 s) for 2 supports (horizontal position) 50 kA (1 s) (horizontal position)
Permissible current	1880 A at 35 °C: ≤ IP31 1670 A at 35 °C: > IP31
Busbar cross section	120 x 10 mm
Length	2000 mm
Height	200 mm
Net weight	21.9 kg
Type of busbar connection	Without hole
Support thickness	10 mm

Environment

Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	21.7 kg
Package 1 Height	2 cm
Package 1 width	18 cm
Package 1 Length	212 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product