

Product data sheet

Characteristics

04012

LINERGY FM 1P+N DIS.BLOCK 200A 24M
24HOLES



Main

Range	Linergy
Range of product	Linergy
Product or component type	Device feeder
Product name	Linergy FM
Range compatibility	Prisma G enclosure Prisma P enclosure Prisma PH enclosure
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

Complementary

Mounting support	Slotted backplate DIN rail Plain backplate
Mounting mode	By screws Clip-on
Installed device	Modular device
Poles description	1P + N
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	200 A
[In] rated current	200 A at 40 °C
[Ipk] rated peak withstand current	20 kA
I ² t on activation	6700000 A ² .s
Connections - terminals	Supply: crimped lug50 mm ² Supply: flexible bars, 20 x 3 mm Distribution: quick-connect terminal strips (phase) , 12 x 4...10 mm ² (flexible) Distribution: quick-connect terminal strips (phase) , 12 x 4...10 mm ² (rigid) Distribution: quick-connect terminal strips (neutral) , 18 x 4...10 mm ² (flexible) Distribution: quick-connect terminal strips (neutral) , 18 x 4...10 mm ² (rigid)
9 mm pitches	48
Total number of 18 mm modules	24
Net weight	1.02 kg
Colour	Anthracite grey (RAL 7016)

Environment

Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma IEC 60947-7-1
Product certifications	ASEFA

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.01 kg
Package 1 Height	6 cm
Package 1 width	7.5 cm
Package 1 Length	45 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Weight	6.05 kg
Package 2 Height	7 cm
Package 2 width	28 cm
Package 2 Length	45 cm
Unit Type of Package 3	P06
Number of Units in Package 3	120
Package 3 Weight	122.4 kg
Package 3 Height	70 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------