

# Product data sheet

## Characteristics

# 04013

## LINERGY FM 3P DIS.BLOCK 200A 24M 42HOLES



### Main

Range	Linergy
Range of product	Linergy
Product or component type	Device feeder
Product name	Linergy FM
Range compatibility	Prisma G enclosure Prisma P enclosure Prisma PH enclosure
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

### Complementary

Mounting support	Plain backplate DIN rail Slotted backplate
Installed device	Modular device
Poles description	3P
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	200 A
[In] rated current	200 A at 40 °C
[Ipk] rated peak withstand current	20 kA
I <sup>2</sup> t on activation	6700000 A <sup>2</sup> .s
Connections - terminals	Supply: crimped lug50 mm <sup>2</sup> Supply: flexible bars, 20 x 3 mm Distribution: quick-connect terminal strips (phase) , 12 x 4...10 mm <sup>2</sup> (flexible) Distribution: quick-connect terminal strips (phase) , 12 x 4...10 mm <sup>2</sup> (rigid) Distribution: quick-connect terminal strips (neutral) , 18 x 4...10 mm <sup>2</sup> (flexible) Distribution: quick-connect terminal strips (neutral) , 18 x 4...10 mm <sup>2</sup> (rigid)
9 mm pitches	48
Total number of 18 mm modules	24
Net weight	1.32 kg
Colour	Anthracite grey (RAL 7016)

### Environment

Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma IEC 60947-7-1
Product certifications	ASEFA

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.28 kg
Package 1 Height	6.7 cm
Package 1 width	7.6 cm
Package 1 Length	44.7 cm

Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	6.41 kg
Package 2 Height	6.7 cm
Package 2 width	37.6 cm
Package 2 Length	44.7 cm
Unit Type of Package 3	P06
Number of Units in Package 3	120
Package 3 Weight	158.4 kg
Package 3 Height	97 cm
Package 3 width	80 cm
Package 3 Length	60 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

### Contractual warranty

Warranty	18 months
----------	-----------