



Main	
Range	Linergy
Range of product	Linergy
Product or component type	Device feeder
Product name	Linergy FM
Range compatibility	Prisma G enclosure Prisma P enclosure Prisma PH enclosure
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

Complementary

Mounting support	DIN rail
	Plain backplate
	Slotted backplate
Installed device	Modular device
Poles description	3P + N
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[le] rated operational current	200 A
[In] rated current	200 A at 40 °C
[lpk] rated peak withstand current	20 kA
I²t on activation	6700000 A².s
Connections - terminals	Supply: crimped lug50 mm²
	Supply: flexible bars, 20 x 3 mm
	Distribution: quick-connect terminal strips (phase), 12 x 410 mm² (flexible)
	Distribution: quick-connect terminal strips (phase), 12 x 410 mm² (rigid)
	Distribution: quick-connect terminal strips (neutral), 18 x 410 mm ² (flexible)
	Distribution: quick-connect terminal strips (neutral), 18 x 410 mm² (rigid)
9 mm pitches	48
Total number of 18 mm modules	24
Net weight	1.6 kg
Colour	Anthracite grey (RAL 7016)

Environment

Standards	IEC 61439-1, inside Prisma	
otandardo	IEC 61439-2, inside Prisma	
	IEC 60947-7-1	
Product certifications	ASEFA	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	1.6 kg	
Package 1 Height	6.8 cm	
Package 1 width	8 cm	
Package 1 Length	44.6 cm	

Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	7.9 kg
Package 2 Height	6.8 cm
Package 2 width	38 cm
Package 2 Length	44.6 cm
Unit Type of Package 3	P06
Number of Units in Package 3	120
Package 3 Weight	192 kg
Package 3 Height	97 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------