



Main

Range	Acti9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L + N
Length in 18 mm modules	12

Complementary

Number of ways	4 ways N + 3 L
Poles configuration for 1 way	1 x 3P + N
Connection pitch	9 Mm between phase and neutral 18 mm between phases
Connector type	Tooth
Distance between way	54 mm
Insulation	Insulated
Device presentation	Cuttable
Provided equipment	2 end piece
[Ie] rated operational current	80 A at 40 °C
[Ue] rated operational voltage	230 V AC 50/60 Hz Ph/N 400 V AC 50/60 Hz Ph/Ph
[Ui] rated insulation voltage	440 V AC conforming to IEC 61439-1
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	24
Height	30 mm
Width	218 mm
Depth	27 mm
Net weight	160 g
Colour	White (RAL 9003)
Range compatibility	Acti9 iC40

Environment

Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3

Offer Sustainability

RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product
