



### Main

Range	Acti9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L + N
Length in 18 mm modules	48

### Complementary

Number of ways	4 ways N + 3 L (balanced)
Poles configuration for 1 way	3P + N
Connection pitch	9 Mm between phase and neutral 18 mm between phases
Connector type	Tooth
Distance between way	54 mm
Insulation	Insulated
Device presentation	Cuttable
Provided equipment	2 end piece
[Ie] rated operational current	80 A at 40 °C
[Ue] rated operational voltage	230 V Ph/N 400 V Ph/Ph
[Ui] rated insulation voltage	440 V
[Uimp] rated impulse withstand voltage	4 kV
Mounting mode	Horizontal
Mounting location	Top
9 mm pitches	96
Height	30 mm
Width	860 mm
Depth	27 mm
Net weight	685 g
Colour	White (RAL 9003)
Range compatibility	Acti9 iC40

### Environment

Fire resistance	960 °C
Pollution degree	3

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes

---

RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---