



Main

Range	Prisma
Range of product	Prisma P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	Prisma P cubicle
Type of front plate	Cut-out
Installed device	ComPact: fixed NSX400 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX400 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX400 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX400 without earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX400 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX400 without earth leakage protection - control: motor mechanism - vertical installation ComPact: drawout NSX400 without earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX400 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX400 without earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX630 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX630 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX630 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX630 without earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX630 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX630 without earth leakage protection - control: motor mechanism - vertical installation ComPact: drawout NSX630 without earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX630 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX630 without earth leakage protection - control: motor mechanism - vertical installation
Poles description	2 x 3P: mounting plate support: NSX400 vertical installation 2 x 4P: mounting plate support: NSX400 vertical installation 2 x 3P: mounting plate support: NSX630 vertical installation 2 x 4P: mounting plate support: NSX630 vertical installation
Operating position	Vertical

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Complementary

Enclosure/cubicle description	Cubicle - width 650 mm depth 400 mm
Connection position	Direct connection Linergy FC
Number of vertical modules [50 mm]	7
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA
Material	Steel
Surface finish	Matt Smooth
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9001)
Height	350 mm
Width	500 mm
Net weight	1.22 kg

Quantity per set	Set of 1
Functional unit	650 mm 400 mm Prisma P cubicle ComPact NSX400 without fixed toggle vertical 3P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without fixed toggle vertical 4P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without plug-in toggle vertical 3P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without plug-in toggle vertical 4P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without fixed direct front rotary handle vertical 3P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without fixed direct front rotary handle vertical 4P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without fixed motor mechanism vertical 3P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without fixed motor mechanism vertical 4P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without plug-in direct front rotary handle vertical 3P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without plug-in direct front rotary handle vertical 4P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without plug-in motor mechanism vertical 3P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without plug-in motor mechanism vertical 4P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without drawout toggle vertical 3P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without drawout toggle vertical 4P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without drawout direct front rotary handle vertical 3P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without drawout direct front rotary handle vertical 4P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without drawout motor mechanism vertical 3P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX400 without drawout motor mechanism vertical 4P 2 direct 11 650 mm 400 mm Prisma P cubicle ComPact NSX630 without fixed toggle vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without fixed toggle vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without plug-in toggle vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without plug-in toggle vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without fixed direct front rotary handle vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without fixed direct front rotary handle vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without fixed motor mechanism vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without fixed motor mechanism vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without plug-in direct front rotary handle vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without plug-in direct front rotary handle vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without plug-in motor mechanism vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without plug-in motor mechanism vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without drawout toggle vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without drawout toggle vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without drawout direct front rotary handle vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without drawout direct front rotary handle vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without drawout motor mechanism vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 without drawout motor mechanism vertical 4P 2 direct 13

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.22 kg
Package 1 Height	3 cm
Package 1 width	36 cm
Package 1 Length	51 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Weight	12.8 kg
Package 2 Height	37 cm
Package 2 width	17 cm
Package 2 Length	53 cm
Unit Type of Package 3	P12
Number of Units in Package 3	80
Package 3 Weight	102.4 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free plastic parts product