03666
PLAST. 2 NSX630 VIGI VERTICAL

Green Premium™ Product

Main

Range	Prisma
Range of product	Prisma P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	Prisma P cubicle
Type of front plate	Cut-out
Installed device	ComPact: fixed NSX400 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX400 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX400 with earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX400 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX400 with earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX400 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX400 with earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX630 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX630 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX630 with earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX630 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX630 with earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX630 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX630 with earth leakage protection - control: motor mechanism - vertical installation
Poles description	2 x 3P: mounting plate support: NSX400 vertical installation 2 x 4P: mounting plate support: NSX400 vertical installation 2 x 3P: mounting plate support: NSX630 vertical installation 2 x 4P: mounting plate support: NSX630 vertical installation
Operating position	Vertical

Complementary

Enclosure/cubicle description	Cubicle - width 650 mm depth 400 mm
Connection position	Linergy FC Direct connection
Number of vertical modules [50 mm]	9
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA
Material	Steel
Surface finish	Smooth Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9001)
Height	450 mm
Width	500 mm
Net weight	1.6 kg
Quantity per set	Set of 1
Functional unit	650 mm 400 mm Prisma P cubicle ComPact NSX400 with fixed toggle vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with fixed toggle vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with plug-in toggle vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with plug-in toggle vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with fixed direct front rotary handle vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with fixed direct front rotary handle vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with plug-in direct front rotary handle vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with plug-in direct front rotary handle vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with drawout toggle vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with drawout toggle vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with drawout direct front rotary handle vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with drawout direct front rotary handle vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with drawout motor mechanism vertical 3P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX400 with drawout motor mechanism vertical 4P 2 direct 13 650 mm 400 mm Prisma P cubicle ComPact NSX630 with fixed toggle vertical 3P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with fixed toggle vertical 4P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with plug-in toggle vertical 3P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with plug-in toggle vertical 4P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with fixed direct front rotary handle vertical 3P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with fixed direct front rotary handle vertical 4P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with plug-in direct front rotary handle vertical 3P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with plug-in direct front rotary handle vertical 4P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with drawout toggle vertical 3P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with drawout toggle vertical 4P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with drawout direct front rotary handle vertical 3P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with drawout direct front rotary handle vertical 4P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with drawout motor mechanism vertical 3P 2 direct 15 650 mm 400 mm Prisma P cubicle ComPact NSX630 with drawout motor mechanism vertical 4P 2 direct 15

Life Is On | Schneider Electric

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.6 kg
Package 1 Height	3 cm
Package 1 width	46 cm
Package 1 Length	51 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Weight	9.96 kg
Package 2 Height	10 cm
Package 2 width	52 cm
Package 2 Length	53 cm
Unit Type of Package 3	P12
Number of Units in Package 3	12
Package 3 Weight	19.92 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free plastic parts product