



Main

Range	Lineryy
Range of product	Prisma Plus System P Prisma Plus System G
Product or component type	Distribution block
Product name	Lineryy DX
Range compatibility	Prisma G Prisma P Prisma PH Pack 160 Prisma Pack 250
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

Complementary

Location of connection	Top
Mounting support	DIN rail
Poles description	4P
[Ue] rated operational voltage	440 V AC
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	63 A at 40 °C
[In] rated current	63 A at 40 °C
Connections - terminals	Supply: tunnel type terminal 16 mm ² (flexible) Supply: tunnel type terminal 25 mm ² (rigid) Distribution: spring terminal (phase) , 12 x 2.5...6 mm ² (flexible) Distribution: spring terminal (phase) , 12 x 2.5...6 mm ² (rigid) Distribution: spring terminal (neutral) , 12 x 2.5...6 mm ² (flexible) Distribution: spring terminal (neutral) , 12 x 2.5...6 mm ² (rigid)
9 mm pitches	8
Total number of 18 mm modules	4
Net weight	0.29 kg

Environment

Pollution degree	3
Resistance to incandescent wire	960 °C conforming to IEC 60695-2-11
Standards	IEC 60947-7-1 IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	320 g
Package 1 Height	7.5 cm
Package 1 width	7.5 cm
Package 1 Length	10 cm
Unit Type of Package 2	S03
Number of Units in Package 2	30

Package 2 Weight	10.098 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------