



Main

Range	Linergy
Range of product	Linergy
Product or component type	Distribution block
Product name	Linergy DX
Range compatibility	Prisma G enclosure Prisma P enclosure Prisma PH enclosure Prisma Pack 160 enclosure Prisma Pack 250 enclosure
Accessory / separate part category	Current distribution accessory
IP degree of protection	IPxx B

Complementary

Mounting support	DIN rail
Installed device	Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed C120 without earth leakage protection - control: toggle Acti 9: fixed iC120 with earth leakage protection - control: toggle Acti 9: fixed iC120 without earth leakage protection - control: toggle ComPact: fixed INS40 - control: direct front rotary handle - vertical installation ComPact: fixed INS63 - control: direct front rotary handle - vertical installation ComPact: fixed INS100 - control: direct front rotary handle - vertical installation ComPact: fixed INS125 - control: direct front rotary handle - vertical installation ComPact: fixed INS160 - control: direct front rotary handle - vertical installation Multi 9: fixed NG125 with earth leakage protection - control: toggle Multi 9: fixed NG125 without earth leakage protection - control: toggle Multi 9: fixed NG125 NA - control: toggle ComPact: fixed NG160 with earth leakage protection - control: toggle ComPact: fixed NG160 without earth leakage protection - control: toggle ComPact: fixed NG160 NA without earth leakage protection - control: toggle ComPact: fixed NSXm without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSXm with earth leakage protection - control: toggle - vertical installation
Poles description	4P
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	125 A at 40 °C
[Icw] rated short-time withstand current	4.5 kA for 1 s
[Ipk] rated peak withstand current	20 kA
I ² t on activation	20250000 A ² .s
Connections - terminals	Supply: tunnel type terminal 35 mm ² (rigid) Supply: tunnel type terminal 35 mm ² (flexible) Distribution: spring terminal, 2 x 4...10 mm ² (flexible) Distribution: spring terminal, 2 x 4...10 mm ² (rigid) Distribution: spring terminal, 3 x 2.5...6 mm ² (flexible) Distribution: spring terminal, 3 x 2.5...6 mm ² (rigid) Distribution: spring terminal, 7 x 1.5...4 mm ² (flexible) Distribution: spring terminal, 7 x 1.5...4 mm ² (rigid) Distribution: tunnel type terminal, 1 x 4...16 mm ² (flexible) Distribution: tunnel type terminal, 1 x 4...25 mm ² (rigid)
9 mm pitches	12
Height	127 mm
Width	108 mm

Depth	48 mm
Net weight	0.5 kg
Colour	Anthracite grey (RAL 7016)

Environment

Pollution degree	3
Resistance to incandescent wire	960 °C conforming to IEC 60695-2-11
Standards	IEC 60947-7-1 IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma
Product certifications	ASEFA
Ambient air temperature for operation	-25...55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	500 g
Package 1 Height	9.8 cm
Package 1 width	11.2 cm
Package 1 Length	13.5 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Weight	2.58 kg
Package 2 Height	12 cm
Package 2 width	15 cm
Package 2 Length	50 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	2.58 kg
Package 3 Height	12 cm
Package 3 width	15 cm
Package 3 Length	50 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------