



Main

Range	Prisma
Range of product	Prisma G Prisma P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	Prisma G enclosure Prisma P cubicle
Type of front plate	Cut-out
Installed device	ComPact: fixed INS320...400 - control: direct front rotary handle - vertical installation ComPact: fixed INS500...630 - control: direct front rotary handle - vertical installation ComPact: fixed INV320...400 - control: direct front rotary handle - vertical installation ComPact: fixed INV500...630 - control: direct front rotary handle - vertical installation
Poles description	1 x 3P: mounting plate support: INS320...400 vertical installation 1 x 4P: mounting plate support: INS320...400 vertical installation 1 x 3P: mounting plate support: INS500...630 vertical installation 1 x 4P: mounting plate support: INS500...630 vertical installation 1 x 3P: mounting plate support: INV320...400 vertical installation 1 x 4P: mounting plate support: INV320...400 vertical installation 1 x 3P: mounting plate support: INV500...630 vertical installation 1 x 4P: mounting plate support: INV500...630 vertical installation
Operating position	Vertical

Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm
Connection position	Direct connection Linergy FC
Number of vertical modules [50 mm]	10
Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASEFA
Material	Steel
Surface finish	Smooth Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9001)
Height	500 mm
Width	500 mm
Net weight	1.9 kg

Quantity per set	Set of 1
Functional unit	650 mm 400 mm Prisma P cubicle ComPact INS320...400 fixed direct front rotary handle vertical 3P 1 direct 10 650 mm 400 mm Prisma P cubicle ComPact INS320...400 fixed direct front rotary handle vertical 4P 1 direct 10 650 mm 400 mm Prisma P cubicle ComPact INS500...630 fixed direct front rotary handle vertical 3P 1 direct 11 650 mm 400 mm Prisma P cubicle ComPact INS500...630 fixed direct front rotary handle vertical 4P 1 direct 11 650 mm 400 mm Prisma P cubicle ComPact INV320...400 fixed direct front rotary handle vertical 3P 1 direct 10 650 mm 400 mm Prisma P cubicle ComPact INV320...400 fixed direct front rotary handle vertical 4P 1 direct 10 650 mm 400 mm Prisma P cubicle ComPact INV500...630 fixed direct front rotary handle vertical 3P 1 direct 11 650 mm 400 mm Prisma P cubicle ComPact INV500...630 fixed direct front rotary handle vertical 4P 1 direct 11 600 mm Prisma G floor-standing enclosure ComPact INS320...400 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 10 600 mm Prisma G wall-mounted enclosure ComPact INS320...400 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 10 600 mm Prisma G floor-standing enclosure ComPact INS320...400 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 10 600 mm Prisma G wall-mounted enclosure ComPact INS320...400 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 10 600 mm Prisma G floor-standing enclosure ComPact INS500...630 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 12 600 mm Prisma G wall-mounted enclosure ComPact INS500...630 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 12 600 mm Prisma G floor-standing enclosure ComPact INS500...630 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 12 600 mm Prisma G wall-mounted enclosure ComPact INS500...630 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 12 600 mm Prisma G floor-standing enclosure ComPact INV320...400 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 10 600 mm Prisma G wall-mounted enclosure ComPact INV320...400 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 10 600 mm Prisma G floor-standing enclosure ComPact INV320...400 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 10 600 mm Prisma G wall-mounted enclosure ComPact INV320...400 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 10 600 mm Prisma G floor-standing enclosure ComPact INV500...630 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 12 600 mm Prisma G wall-mounted enclosure ComPact INV500...630 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 12 600 mm Prisma G floor-standing enclosure ComPact INV500...630 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 12 600 mm Prisma G wall-mounted enclosure ComPact INV500...630 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 12

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.9 kg
Package 1 Height	3 cm
Package 1 width	51 cm
Package 1 Length	51 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Weight	11.769 kg
Package 2 Height	10 cm
Package 2 width	52 cm
Package 2 Length	53 cm
Unit Type of Package 3	P12
Number of Units in Package 3	72
Package 3 Weight	141.228 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free plastic parts product