



Main

Range	Prisma
Range of product	Prisma G Prisma P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	Prisma Pack 160 enclosure Prisma G enclosure Prisma P cubicle
Type of front plate	Transparent
Installed device	TeSys: fixed TeSys U - horizontal installation TeSys: fixed GV2 + D or K contactors <= 40 A - horizontal installation PowerLogic: iEM3000 PowerLogic: PM3000
Poles description	9 x 3P: modular rail support: TeSys U horizontal installation 9 x 3P: modular rail support: GV2 + D or K contactors <= 40 A horizontal installation
Operating position	Horizontal

Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm Pack enclosure - width 555 mm
Connection position	Direct connection
Number of vertical modules [50 mm]	4
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA
Material	Glass
Surface finish	Smooth Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9001)
Height	200 mm
Width	500 mm
Net weight	0.98 kg

Quantity per set	Set of 1
Functional unit	600 mm Prisma G floor-standing enclosure TeSys GV2 + D or K contactors <= 40 A fixed horizontal 3P 9 direct 5 600 mm Prisma G wall-mounted enclosure TeSys GV2 + D or K contactors <= 40 A fixed horizontal 3P 9 direct 5 650 mm 400 mm Prisma P cubicle TeSys GV2 + D or K contactors <= 40 A fixed horizontal 3P 9 direct 5 650 mm 400 mm Prisma P cubicle PowerLogic 3 4 650 mm 400 mm Prisma P cubicle PowerLogic 4 4 600 mm Prisma G floor-standing enclosure TeSys TeSys U fixed horizontal 3P 9 direct 5 600 mm Prisma G wall-mounted enclosure TeSys TeSys U fixed horizontal 3P 9 direct 5 600 mm Prisma G floor-standing enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4 600 mm Prisma G wall-mounted enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4 650 mm 400 mm Prisma P cubicle TeSys TeSys U fixed horizontal 3P 9 direct 4 555 mm Pack 160 Pack enclosure TeSys GV2 + D or K contactors <= 40 A fixed horizontal 3P 9 direct 5 555 mm Pack 160 Pack enclosure TeSys TeSys U fixed horizontal 3P 9 direct 5 555 mm Pack 160 Pack enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.1 kg
Package 1 Height	4 cm
Package 1 width	21 cm
Package 1 Length	52 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Weight	8.28 kg
Package 2 Height	16.8 cm
Package 2 width	22.9 cm
Package 2 Length	52.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile