



Main

Range	Prisma
Range of product	Prisma G
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	Prisma G enclosure
Type of front plate	Cut-out
Type of front plate	Cut-out
Installed device	Human-switchboard interface: 96 x 96 mm device Human-switchboard interface: HSI PowerLogic: PM400...800 Enerlin'X: FDM121

Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 850 mm
Number of vertical modules [50 mm]	3
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA
Surface finish	Matt Smooth
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9001)
Height	150 mm
Net weight	0.46 kg
Quantity per set	Set of 1
Functional unit	850 mm Prisma G floor-standing enclosure human-switchboard interface 96 x 96 mm device 4 3 850 mm Prisma G floor-standing enclosure human-switchboard interface HSI 4 3 850 mm Prisma G floor-standing enclosure PowerLogic 4 3 850 mm Prisma G floor-standing enclosure Enerlin'X FDM121 4 3

Packing Units

Package 1 Weight	1.098 kg
Package 1 Height	2.000 cm
Package 1 width	16.000 cm
Package 1 Length	76.000 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free plastic parts product