



### Main

Range	Prisma
Range of product	Prisma P
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	Prisma P cubicle
Installation description	Cubicle - width 650 mm depth 800 mm Cubicle + duct - width 650 mm depth 400 mm
Installed device	ComPact: fixed NS630b...1000 - control: toggle - horizontal installation ComPact: fixed NS630b...1000 - control: direct front rotary handle - horizontal installation
Poles description	1 x 3P: fixed NS630b...1000 horizontal installation 1 x 4P: fixed NS630b...1000 horizontal installation
Number of vertical modules [50 mm]	7 module(s): NS630b...1000, front connection in 650 mm Widecubicle + duct 8 module(s): NS630b...1000, connection transfer assembly in 650 mm Widecubicle + duct 7 module(s): NS630b...1000, rear connection in 650 mm Widecubicle
Standards	IEC 61439-2
Product certifications	ASEFA

### Complementary

Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Matt Smooth
Colour	White (RAL 9001)
Width	650 mm
Height	350 mm
Net weight	2.84 kg
Functional unit	650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed toggle horizontal 3P 1 front connection 7 12.5 mm 650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed toggle horizontal 3P 1 connection transfer assembly 8 12.5 mm 650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed direct front rotary handle horizontal 3P 1 front connection 7 12.5 mm 650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed direct front rotary handle horizontal 3P 1 connection transfer assembly 8 12.5 mm 650 mm 800 mm Prisma P cubicle ComPact NS630b...1000 fixed toggle horizontal 3P 1 rear connection 7 12.5 mm 650 mm 800 mm Prisma P cubicle ComPact NS630b...1000 fixed direct front rotary handle horizontal 3P 1 rear connection 7 12.5 mm 650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed toggle horizontal 4P 1 front connection 7 12.5 mm 650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed toggle horizontal 4P 1 connection transfer assembly 8 12.5 mm 650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed direct front rotary handle horizontal 4P 1 front connection 7 12.5 mm 650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed direct front rotary handle horizontal 4P 1 connection transfer assembly 8 12.5 mm 650 mm 800 mm Prisma P cubicle ComPact NS630b...1000 fixed toggle horizontal 4P 1 rear connection 7 12.5 mm 650 mm 800 mm Prisma P cubicle ComPact NS630b...1000 fixed direct front rotary handle horizontal 4P 1 rear connection 7 12.5 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.84 kg
Package 1 Height	4.5 cm
Package 1 width	35 cm
Package 1 Length	58 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Halogen content performance	Halogen free plastic parts product