



Main

Range	Prisma
Range of product	Prisma P
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	Prisma P cubicle
Installation description	Cubicle - width 650 mm depth 400 mm
Mounting plate description	Busbar
Installed device	FuPact: fixed ISFL160 - control: fuse carriers handle - vertical installation
Poles description	9 x 3P: fixed ISFL160 vertical installation
Number of vertical modules [50 mm]	11 module(s): ISFL160, rear connection on busbar in 650 mm Widecubicle
Standards	IEC 61439-2
Product certifications	ASEFA

Complementary

Connections - terminals	Cable ISFL160 bottom 87.5 mm Cable ISFL160 top 62.5 mm
Colour	White (RAL 9001)
Width	70 mm
Height	625 mm
Depth	365 mm
Net weight	2.44 kg
Functional unit	650 mm 400 mm Prisma P cubicle FuPact ISFL160 fixed fuse carriers handle vertical 3P 9 rear connection on busbar 11 0.2 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.44 kg
Package 1 Height	4.5 cm
Package 1 width	8.5 cm
Package 1 Length	43 cm
Unit Type of Package 2	P12
Number of Units in Package 2	22
Package 2 Weight	53.68 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Halogen content performance	Halogen free product