



### Main

Range	Prisma
Range of product	Prisma P
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	Prisma P cubicle
Installation description	Cubicle - width 650 mm depth 400 mm
Mounting plate description	Busbar
Installed device	FuPact: fixed ISFL160 - control: fuse carriers handle - vertical installation FuPact: fixed ISFL250...630 - control: fuse carriers handle - vertical installation
Poles description	10 x 3P: fixed ISFL160 vertical installation 5 x 3P: fixed ISFL250...630 vertical installation
Number of vertical modules [50 mm]	24 module(s): ISFL160, rear connection on busbar in 650 mm Widecubicle 24 module(s): ISFL250...630, rear connection on busbar in 650 mm Widecubicle
Standards	IEC 61439-2
Product certifications	ASEFA

### Complementary

Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Matt Smooth
Colour	White (RAL 9001)
Width	70 mm
Height	625 mm
Depth	365 mm
Net weight	5.06 kg
Functional unit	650 mm 400 mm Prisma P cubicle FuPact ISFL160 fixed fuse carriers handle vertical 3P 10 rear connection on busbar 24 512.5 mm 650 mm 400 mm Prisma P cubicle FuPact ISFL250...630 fixed fuse carriers handle vertical 3P 5 rear connection on busbar 24 512.5 mm

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5.06 kg
Package 1 Height	10 cm
Package 1 width	12.5 cm
Package 1 Length	67 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Halogen content performance	Halogen free plastic parts product