



Main

Range	Prisma
Range of product	Prisma P
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	Prisma P cubicle
Installation description	Cubicle - width 650 + 150 mm depth 400 mm
Provided equipment	Gasket not included
Mounting location	Bottom of enclosure VarPlus Can VarplusCan first 480 mm Bottom of enclosure VarPlus Can VarplusCan second 325 mm Bottom of enclosure VarPlus Can VarplusCan + detuned reactors first 155 mm Bottom of enclosure VarPlus Can VarplusCan + detuned reactors second 300 mm
Mounting plate description	Dedicated
Installed device	Power factor correction: fixed VarPlus Can - horizontal installation
Number of vertical modules [50 mm]	36 module(s): VarPlus Can in 650 + 150 mm Widecubicle (cable coming from top or bottom of enclosure)
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Complementary

Colour	White (RAL 9001)
Width	550 mm
Height	235 mm
Depth	365 mm
Net weight	0 kg
Functional unit	650 + 150 mm 400 mm Prisma P cubicle power factor correction VarPlus Can fixed horizontal 4 36 0.1 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5.28 kg
Package 1 Height	5 cm
Package 1 width	24 cm
Package 1 Length	55 cm
Unit Type of Package 2	P12
Number of Units in Package 2	48
Package 2 Weight	265.44 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free plastic parts product