



### Main

Range	Spacial
Product or component type	Drive flush mounting kit
Accessory category	Mounting and fixing accessory
Product specific application	Process and utilities
Range compatibility	Spacial SF and SM enclosures: H: $\geq$ 400 mm x W: $\geq$ 300 mm Spacial S3D enclosure: H: $\geq$ 400 mm x W: $\geq$ 300 mm Altivar variable speed drive ATV630 Altivar variable speed drive ATV930
Compatibility for Altivar Process 630-930, size:	1
Motor power kW	0.75 KW 220/240 V 1.5 KW 220/240 V 2.2 KW 220/240 V 3 KW 220/240 V 4 KW 220/240 V 0.75 KW 380/480 V 1.5 KW 380/480 V 2.2 KW 380/480 V 3 KW 380/480 V 4 KW 380/480 V 5.5 KW 380/480 V
Mounting location	Mode 1: back of enclosure on mounting plate Mode 2: inside enclosure
Kit composition	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating. Fixing by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic.

### Complementary

Permanent permissible load	4.8 kg
Colour	Grey (RAL 7035)
Height	360 Mm external: 307 mm cut-out:
Width	235 Mm external: 190 mm cut-out:
Depth	22 mm wall-enclosure separation:
Net weight	1.58 kg
Services	Configuration of enclosure pre-drilled back at requested dimensions Factory installation drive flush mounting kit on enclosure

### Environment

IP degree of protection	IP55 conforming to IEC 60529
-------------------------	------------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Package 1 Weight	1.565 kg
Package 1 Height	0.500 dm
Package 1 width	2.560 dm
Package 1 Length	3.780 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>