



Main

Range	Spacial
Product or component type	Drive flush mounting kit
Accessory category	Mounting and fixing accessory
Product specific application	Process and utilities
Range compatibility	Altivar variable speed drive ATV630 Altivar variable speed drive ATV930 Spacial SF and SM enclosures: H:>=600 mm x W:>=300 mm Spacial S3D enclosure: H:>=600 mm x W:>=300 mm
Compatibility for Altivar Process 630-930, size:	3
Motor power kW	7.5 KW 220/240 V 11 KW 220/240 V 15 KW 380/480 V 18.5 KW 380/480 V 22 kW 380/480 V
Mounting location	Mode 1: back of enclosure on mounting plate Mode 2: inside enclosure
Kit composition	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating. Fixing by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic.

Complementary

Permanent permissible load	14.3 kg
Colour	Grey (RAL 7035)
Height	555 Mm external: 503 mm cut-out:
Width	295 Mm external: 250 mm cut-out:
Depth	22 mm wall-enclosure separation:
Net weight	2.452 kg
Services	Configuration of enclosure pre-drilled back at requested dimensions Factory installation drive flush mounting kit on enclosure

Environment

IP degree of protection	IP55 conforming to IEC 60529
-------------------------	------------------------------

Packing Units

Package 1 Weight	2.442 kg
Package 1 Height	0.480 dm
Package 1 width	3.110 dm
Package 1 Length	5.650 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile