# Product data sheet Characteristics

# NSYSFP20750T

Spacial SFP 2000x700x500mm, IP 55, RAL7035, glazed door for Prisma P system





# Main

Range	Spacial
Extended range	Spacial SF
Application	Prisma application
Product or component type	Suitable enclosure
Enclosure nominal height	2000 mm
Enclosure nominal width	700 mm
Enclosure nominal depth	500 mm
Enclosure mounting	Floor-standing
Product specific application	Installing the Prisma Plus System P
Device composition	2 sliding rails 4 mounting plate bracket 1 structure 1 door 1 locking system with handle: door 1 rear panel 1 roof 4 adaptor upright

#### Complementary

Structure type	Perforated structure with a pitch of 25 mm
Citation type	Panels and doors built into the structure
	Formed from a single section
	Vertical uprights joined with top and bottom frames
Door type	Glazed front
Number of doors	Front: 1 door(s)
Door opening side	Reversible (120 °)
Lock type	4 points lock, handle with 5 mm double bar insert front door
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Accessibility for operation	Front
	Rear
	Sides of enclosure
Removable parts	Door by screws hinge
	Rear panel by screws
	Roof by screws
	Mounting plate bracket by screws
	Sliding rail by screws
	Adaptor upright by screws
Material	Frame: galvanised steel
	Uprights: galvanised steel
	Door: Securit glass
	Door: sheet steel
	Panels: sheet steel
	Hinge: zamak Handle: polyamide 6 with 30 % fibre glass
Surface finish	Epoxy-polyester powder
Colour	Enclosure: grey (RAL 7035)
	Handle: black (RAL 9005)

#### Environment

Standards	IEC 62208
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	97 kg	
Package 1 Height	213 cm	
Package 1 width	75 cm	
Package 1 Length	59 cm	

## Offer Sustainability

Green Premium product
☑REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
₫Yes
China RoHS Declaration
Product Environmental Profile

#### Contractual warranty

Marranty	10
Warrantv	18 months
Transity	TO MONUTO