



### Main

Range	Prisma
Range of product	Prisma P
Product or component type	Door
Range compatibility	Prisma P cubicle duct
Provided equipment	Door Handle Keylock (key 405) Other keylock and insert to be ordered separately 2 hinge
Enclosure mounting	Floor-standing
Type of door	Transparent
IP degree of protection	IP30

### Complementary

Installation description	Cubicle duct - width 400 mm
Door opening side	Reversible
Number of locks	2
Door opening angle	120 °
Number of vertical modules [50 mm]	36
Enclosure material	Glass Treated sheet steel
Quantity per set	Set of 1
Height	2000 mm
Width	400 mm
Depth	30 mm
Net weight	12 kg
Surface finish	Smooth Matt
Colour	White (RAL 9001)

### Environment

IK degree of protection	IK08 conforming to EN/IEC 62262
Standards	IEC 61439-1 IEC 61439-2
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	12 kg
Package 1 Height	8 cm
Package 1 width	41 cm
Package 1 Length	203 cm
Unit Type of Package 2	P2M
Number of Units in Package 2	20
Package 2 Weight	240 kg
Package 2 Height	95 cm

Package 2 width	120 cm
Package 2 Length	200 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>