



Main

Range	Prisma
Range of product	Prisma P
Product or component type	Door
Range compatibility	Prisma P cubicle duct
Provided equipment	Door Handle Keylock (key 405) Other keylock and insert to be ordered separately 4 hinge Polyurethane joint
Enclosure mounting	Floor-standing
Type of door	Transparent
IP degree of protection	IP55

Complementary

Installation description	Cubicle duct - width 400 mm
Door opening side	Reversible
Number of locks	3
Door opening angle	120 °
Number of vertical modules [50 mm]	36
Enclosure material	Glass Treated sheet steel
Quantity per set	Set of 1
Height	2000 mm
Width	400 mm
Depth	30 mm
Net weight	18.18 kg
Surface finish	Matt Smooth
Colour	White (RAL 9001)

Environment

IK degree of protection	IK10 conforming to EN/IEC 62262
Standards	IEC 61439-1 IEC 61439-2
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	18.18 kg
Package 1 Height	8 cm
Package 1 width	44 cm
Package 1 Length	203.5 cm
Unit Type of Package 2	P2M
Number of Units in Package 2	10
Package 2 Weight	181.8 kg
Package 2 Height	63 cm

Package 2 width	120 cm
Package 2 Length	200 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information