



Main

Range	Prisma
Range of product	Prisma P
Product or component type	Door
Range compatibility	Prisma P cubicle duct
Provided equipment	Door Other keylock and insert to be ordered separately 2 hinge Black handle with lock for 405 key
Enclosure mounting	Floor-standing
Type of door	HSI cut-out
IP degree of protection	IP30

Complementary

Installation description	Cubicle duct - width 400 mm
Door opening side	Reversible
Number of locks	2
Door opening angle	120 °
Number of vertical modules [50 mm]	36
Additional information	Can be equipped with front plates for 72 x 72 mm or 96 x 96 mm instruments
Quantity per set	Set of 1
Height	2000 mm
Width	400 mm
Net weight	10.4 kg
Surface finish	Smooth Matt
Colour	White (RAL 9001)

Environment

IK degree of protection	IK08 conforming to EN/IEC 62262
Standards	IEC 61439-1 IEC 61439-2
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	10.4 kg
Package 1 Height	6 cm
Package 1 width	44 cm
Package 1 Length	203.5 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	10
Package 2 Weight	104 kg
Package 2 Height	47 cm
Package 2 width	203 cm
Package 2 Length	120 cm
Unit Type of Package 3	P2M

Number of Units in Package 3	10
Package 3 Weight	104 kg
Package 3 Height	47 cm
Package 3 width	120 cm
Package 3 Length	203 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information