



### Main

Range	Linergy
Range of product	Linergy BS
Product or component type	Insulating plate
Accessory / separate part category	Insulation accessory
Range compatibility	Linergy BS busbar Prisma G duct Prisma P duct
IP degree of protection	IPxx B
Barrier position	Front

### Complementary

Installation description	Wall-mounted duct - width 300 mm Floor-standing duct - width 300 mm Duct - width 400 mm
Number of vertical modules [50 mm]	30
Installed device	Multi-stage busbar
[Ie] rated operational current	630 A
Quantity per set	Set of 1
Material	Plastic
Height	1500 mm
Width	250 mm
Net weight	0.74 kg
Colour	Transparent

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	550 g
Package 1 Height	1.5 cm
Package 1 width	23.4 cm
Package 1 Length	151 cm
Unit Type of Package 2	P2M
Number of Units in Package 2	240
Package 2 Weight	177.6 kg
Package 2 Height	75 cm
Package 2 width	120 cm
Package 2 Length	200 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>