



Main

Range	Masterpact
Device short name	OF PF Micro switch SDE
Product or component type	Auxiliary contact block
Device application	Control
Range compatibility	Masterpact MTZ1 circuit breaker

Complementary

Auxiliary contacts type	Standard
Signal contacts composition	4 NO/NC
Breaking capacity	6 A AC-12 240/380 V AC 50/60 Hz 0.5 A DC-12 125 V DC 6 A AC-12 480 V AC 50/60 Hz 6 A AC-12 690 V AC 50/60 Hz 2.5 A DC-12 24/48 V DC 0.3 A DC-12 250 V DC
Minimum load	100 mA at 24 V

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.