



Main

Product or component type	SDX output module
Device short name	SDx
Device application	Breaker status monitoring
Range compatibility	ComPact NSXm earth leakage circuit breaker
Signal contacts composition	2 NO/NC for fault 2 NO/NC for alarm

Complementary

Fault type	Overload Earth leakage
Local signalling	1 LED (green) for ON status 2 LEDs (red) for output status
[Ie] rated operational current	AC-15: 5 A at 80 V AC 50/60 Hz AC-15: 1.74 A at 230 V AC 50/60 Hz AC-15: 0.3 A at 250 V AC 50/60 Hz DC-13: 5 A at 10 V DC DC-13: 2.08 A at 24 V DC DC-13: 0.3 A at 160 V DC
[Ue] rated operational voltage	24...240 V AC/DC
Auxiliary connection terminal	Spring 0.5...1.5 mm ² copper
Wire stripping length	8 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	150 g
Package 1 Height	3 cm
Package 1 width	9 cm
Package 1 Length	16.6 cm
Unit Type of Package 2	S02
Number of Units in Package 2	18
Package 2 Weight	3 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins