

Product data sheet

Characteristics

A9L16619

Acti 9 - iSR remote signal auxiliary Surge Arrester



Main

Range of product	Acti 9
Product or component type	Remote indication auxiliary
Device short name	ISR
Signal contacts composition	1 C/O
[In] rated current	3 A: 380...415 V AC - 50/60 Hz 6 A: 220...240 V AC - 50/60 Hz 1 A: 130 V DC 1.5 A: 60 V DC 2 A: 48 V DC 6 A: 24 V DC
9 mm pitches	1

Complementary

Range compatibility	Acti 9 iQuick PF Acti 9 iQuick PRD Acti 9 iPF Acti 9 iPRC
Mounting mode	Fixed
Mounting support	DIN rail
Height	84 mm
Width	9 mm
Depth	69 mm
Colour	White
Connections - terminals	Clamp terminal (bottom) 3 cable(s) 0.16 mm ² - rigid Clamp terminal (bottom) 6 cable(s) 0.16 mm ² - flexible Clamp terminal (bottom) 1 cable(s) 0.16 mm ² - flexible with ferrule
Wire stripping length	9 mm
Tightening torque	1 N.M 1.2 N.m

Environment

Standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	39 g
Package 1 Height	2 cm
Package 1 width	8 cm
Package 1 Length	9.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	517 g

Package 2 Height	10 cm
Package 2 width	5 cm
Package 2 Length	27 cm
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Weight	5.14 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------