

Product data sheet

Characteristics

M9A26927

Multi9 - fault contact - 1 SD - 240/415 V AC - 24/130 V DC



Main

Range of product	Multi 9
Product or component type	Fault contact
Device short name	SD
Signal contacts composition	1 C/O
[In] rated current	3 A: 415 V AC - 50/60 Hz 6 A: <= 240 V AC - 50/60 Hz 6 A: 24 V DC 2 A: 48 V DC 1.5 A: 60 V DC 1 A: 130 V DC
[Uc] control circuit voltage	240...415 V AC 50/60 Hz 24...130 V DC
9 mm pitches	1

Complementary

Range compatibility	Multi 9 C60 C60BP Multi 9 C60 C60BPR Multi 9 C60 C60SP Multi 9 GFP Multi 9 C60H-DC
[Ui] rated insulation voltage	500 V
[Uiimp] rated impulse withstand voltage	4 kV
Mounting mode	Fixed
Mounting support	DIN rail
Height	85 mm
Width	9 mm
Depth	73.5 mm
Net weight	30 g
Connections - terminals	Clamp terminal (bottom) 1 cable(s) 2.5 mm ² (AWG 14) - rigid Clamp terminal (bottom) 2 cable(s) 1.5 mm ² (AWG 16) - rigid
Wire stripping length	9 mm for bottom connection
Tightening torque	1 N.m bottom

Environment

Standards	EN/IEC 60947-5-1 EN 62019-2
Product certifications	CSA PCT UL UR CCC
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	39 g
Package 1 Height	2.1 cm
Package 1 width	8 cm
Package 1 Length	9.4 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	526 g
Package 2 Height	10 cm
Package 2 width	9 cm
Package 2 Length	27 cm
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Weight	5.101 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
Circularity Profile	<input checked="" type="checkbox"/> End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins