GVAE11

TeSys GV2 & GV3 - auxiliary contact - 1 NO + 1 NC





Main

Range TeSys Device short name GVAE Product or component type Product compatibility GV2P GV2RT GV2ME GV3L GV2LE GV3P GV2L Mounting location Front side Pole contact 1 NO + 1 NC composition Quantity per set Set of 10		
Product or component type Product compatibility GV2P GV2RT GV2ME GV3L GV2LE GV3P GV2LE GV3P GV2L Mounting location Front side Pole contact composition Auxiliary contact block GV2P GV2RT GV2ME GV3L GV2LE GV3L GV2LE GV3P GV2L Mounting location Front side	Range	TeSys
type Product compatibility GV2P GV2RT GV2ME GV3L GV2LE GV3P GV2L Mounting location Front side Pole contact composition GV2P GV2RT GV2ME GV3ME GV3L GV2LE GV3P GV2L NO + 1 NC	Device short name	GVAE
GV2RT GV2ME GV3L GV2LE GV3P GV2L Mounting location Front side Pole contact composition 1 NO + 1 NC	•	Auxiliary contact block
Pole contact 1 NO + 1 NC composition	Product compatibility	GV2RT GV2ME GV3L GV2LE GV3P
composition	Mounting location	Front side
Quantity per set Set of 10		1 NO + 1 NC
	Quantity per set	Set of 10

Complementary

[Ui] rated insulation voltage	300 V conforming to UL 508 300 V conforming to CSA C22.2 No 14 250 V conforming to IEC 60947-1
[Ue] rated operational voltage	24240 V AC 2460 V DC
[Ith] conventional free air thermal current	2.5 A
Protection type	GG fuse 10 A GB2CB06 circuit breaker 10 A
Mechanical durability	100000 cycles
Minimum switching current	5 mA
Minimum switching voltage	17 V
Rated operational power in VA	120 VA at 110120 V AC-15 - electrical durability: 100000 cycles 120 VA at 230240 V AC-15 - electrical durability: 100000 cycles 48 VA at 24 V AC-15 - electrical durability: 100000 cycles 60 VA at 48 V AC-15 - electrical durability: 100000 cycles
Rated operational power in W	15 W at 48 V DC-13 - electrical durability: 100000 cycles 24 W at 24 V DC-13 - electrical durability: 100000 cycles 9 W at 60 V DC-13 - electrical durability: 100000 cycles
Tightening torque	1.4 N.m - on screw clamp terminals
Height	11 mm
Width	45 mm
Depth	29 mm
Net weight	0.02 kg

Environment

Environmental characteristic	Normal environment	
B 11 11 11		

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	18 g	
Package 1 Height	1.6 cm	
Package 1 width	5.1 cm	
Package 1 Length	8.3 cm	

Unit Type of Package 2	BAG
Number of Units in Package 2	1
Package 2 Weight	18 g
Package 2 Height	1.6 cm
Package 2 width	5.1 cm
Package 2 Length	8.3 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	10
Package 3 Weight	210 g
Package 3 Height	12 cm
Package 3 width	6 cm
Package 3 Length	7 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

_		
1	Warranty	18 months

GVAE11