



Main

| | |
|---------------------------|--|
| Range | TeSys |
| Device short name | GVAE |
| Product or component type | Auxiliary contact block |
| Product compatibility | GV2L GV2P GV2RT GV3P GV2LE GV3L LS1D323 GV2ME |
| Mounting location | Front side |
| Pole contact composition | 2 NO |
| Quantity per set | Set of 10 |

Complementary

| | |
|---|--|
| [Ui] rated insulation voltage | 300 V conforming to UL 508 300 V conforming to CSA C22.2 No 14 250 V conforming to IEC 60947-1 |
| [Ue] rated operational voltage | 24...240 V AC 24...60 V DC |
| [Ith] conventional free air thermal current | 2.5 A |
| Protection type | GG fuse 10 A GB2CB06 circuit breaker 10 A |
| Mechanical durability | 100000 cycles |
| Minimum switching current | 5 mA |
| Minimum switching voltage | 17 V |
| Rated operational power in VA | 120 VA at 110...120 V AC-15 - electrical durability: 100000 cycles 120 VA at 230...240 V AC-15 - electrical durability: 100000 cycles 48 VA at 24 V AC-15 - electrical durability: 100000 cycles 60 VA at 48 V AC-15 - electrical durability: 100000 cycles |
| Rated operational power in W | 15 W at 48 V DC-13 - electrical durability: 100000 cycles 24 W at 24 V DC-13 - electrical durability: 100000 cycles 9 W at 60 V DC-13 - electrical durability: 100000 cycles |
| Height | 13 mm |
| Width | 44.5 mm |
| Depth | 31.5 mm |
| Net weight | 0.05 kg |

Environment

| | |
|------------------------------|--------------------|
| Environmental characteristic | Normal environment |
|------------------------------|--------------------|

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 20 g |
| Package 1 Height | 6.2 cm |
| Package 1 width | 7.2 cm |
| Package 1 Length | 12.1 cm |

| | |
|------------------------------|----------|
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Weight | 207 g |
| Package 2 Height | 6.2 cm |
| Package 2 width | 7.2 cm |
| Package 2 Length | 12.1 cm |
| Unit Type of Package 3 | S01 |
| Number of Units in Package 3 | 100 |
| Package 3 Weight | 2.194 kg |
| Package 3 Height | 15 cm |
| Package 3 width | 15 cm |
| Package 3 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|