

Product data sheet

Characteristics

LV434128

Ethernet switchboard display FDM 128, up to 8 connected devices, screen 115.2 x 86.4 mm, IP65 on front face



Main

Device short name	FDM128
Product or component type	Display module
Accessory / separate part category	Display and signalling accessory
Range compatibility	Masterpact MTZ Masterpact NW MasterPact NT ComPact NSX ComPact NS630b...1600 ComPact NS1600b...3200 PowerPact H PowerPact J PowerPact L PowerPact P PowerPact R Acti 9 Smartlink smart communication module
Product name	Enerlin'X FDM
Function of module	Remote control View network Metering Display alarm

Complementary

Control type	Remote control
Mounting mode	Flush mounting
Mounting support	Surface mount with kit
Display type	Active matrix colour TFT LCD with LED backlight
Display resolution	320 x 240 pixels QVGA
View angle horizontal x vertical	70 x 80°
[Us] rated supply voltage	24 V DC - 15...20 %
Maximum power consumption in W	6.8 W
Standards	CE CSA UL
Height	129 mm
Width	163 mm
Depth	56.5 mm
Accessory / separate part category	Spare part for ComPact NS630b...1600 Spare part for ComPact NS1600b...3200

Environment

IP degree of protection	IP54 IP65 front face:
Ambient air temperature for operation	-10...55 °C

Packing Units

Package 1 Weight	0.846 kg
Package 1 Height	7.000 cm
Package 1 width	18.200 cm
Package 1 Length	27.000 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------