



Main

Range of product	ISFL160
Range	FuPact
Product or component type	Block of 3 current transformers
Device application	Power supply
Range compatibility	Fupact ISFL ISFL160 fuse-switch disconnecter
Poles description	3P
Current transformer ratio	150/1 A
Power consumption in VA	2.5 VA






Complementary

Accessory / separate part category	Measurement accessory
Current transformer type	Measurement class 1
Maximum safety factor	5
[Ue] rated operational voltage	800 V AC 50/60 Hz
IP degree of protection	IP20
Standards	VDE 0414 IEC 60044-1 BS 7626
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...80 °C
Height	328.5 mm
Width	49.5 mm
Depth	30 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	417 g
Package 1 Height	6.2 cm
Package 1 width	7 cm
Package 1 Length	37 cm
Unit Type of Package 2	S04
Number of Units in Package 2	20
Package 2 Weight	9.106 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------