



Main

Range	Masterpact
Product name	Masterpact MTZ2
Device short name	MTZ2 12 H10
Product or component type	Circuit breaker
Device application	Protection
Poles description	3P
Network type	AC
Network frequency	50/60 Hz
Breaking capacity code	H10
Suitability for isolation	Yes conforming to IEC 60947-2
Selectivity category	Category B







Complementary

Control type	Push-button
Mounting mode	Drawout
Mounting support	Base plate Rails
[In] rated current	1250 A at 40 °C
[Ui] rated insulation voltage	1250 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-2
[Icm] rated short-circuit making capacity	105 kA 1150 V AC at 50/60 Hz
[Ue] rated operational voltage	1150 V AC 50/60 Hz conforming to IEC 60947-2
Circuit breaker CT rating	1250 A
Performance level	50 kA Icu at 1150 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service breaking capacity	50 kA at 1150 V AC 50/60 Hz conforming to IEC 60947-2
Mechanical durability	25000 cycles with periodic preventive maintenance conforming to IEC 60947-2
Electrical durability	500 cycles 1150 V AC 50/60 Hz conforming to IEC 60947-2
Connection pitch	115 mm
[Icw] rated short-time withstand current	50 KA 1 s conforming to IEC 60947-2 50 KA 0.5 s conforming to IEC 60947-2 50 KA 3 s
Maximum breaking time	25 ms
Maximum closing response time	70 ms
Height	Drawout circuit breaker without chassis: 300 mm Drawout circuit breaker with chassis: 439 mm
Width	Drawout circuit breaker without chassis: 378 mm Drawout circuit breaker with chassis: 441 mm
Depth	Drawout circuit breaker without chassis: 300 mm Drawout circuit breaker with chassis: 403 mm

Environment

Standards	IEC 60364-8-1 IEC 60947-2
Product certifications	IECEE CB Scheme
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
PVC free	Yes