



### Main

Range	Masterpact
Product name	Masterpact MTZ2
Device short name	MTZ2 40 H2
Product or component type	Circuit breaker
Device application	Protection
Poles description	3P
Network type	AC
Network frequency	50/60 Hz
Breaking capacity code	H2
Suitability for isolation	Yes conforming to IEC 60947-2
Selectivity category	Category B

### Complementary

Control type	Push-button
Mounting mode	Fixed
Mounting support	Base plate Rails
[In] rated current	4000 A at 40 °C
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-2
[Icm] rated short-circuit making capacity	220 KA 220/415 V AC at 50/60 Hz 220 KA 440 V AC at 50/60 Hz 187 KA 500/525 V AC at 50/60 Hz 187 KA 660/690 V AC at 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
Circuit breaker CT rating	4000 A
Performance level	100 KA Icu at 220/415 V AC 50/60 Hz conforming to IEC 60947-2 100 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 85 KA Icu at 500/525 V AC 50/60 Hz conforming to IEC 60947-2 85 KA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service breaking capacity	100 KA at 220/415 V AC 50/60 Hz conforming to IEC 60947-2 100 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2 85 KA at 500/525 V AC 50/60 Hz conforming to IEC 60947-2 85 KA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2
Mechanical durability	20000 cycles with periodic preventive maintenance conforming to IEC 60947-2
Electrical durability	AC-3: 6000 cycles 440/690 V AC 50/60 Hz conforming to IEC 60947-3 2500 Cycles 690 V AC 50/60 Hz conforming to IEC 60947-2 5000 Cycles 440 V AC 50/60 Hz conforming to IEC 60947-2 AC-23A: 2500 cycles 690 V AC 50/60 Hz conforming to IEC 60947-3 AC-23A: 5000 cycles 440 V AC 50/60 Hz conforming to IEC 60947-3
Connection pitch	150 mm
[Icw] rated short-time withstand current	85 KA 0.5 s conforming to IEC 60947-2 85 KA 1 s conforming to IEC 60947-2 75 KA 3 s conforming to IEC 60947-2
Integral instant protection	171...209 kA
Maximum breaking time	25 ms
Maximum closing response time	70 ms
Height	352 mm
Width	422 mm
Depth	300 mm

## Environment

Standards	IEC 60364-8-1 IEC 60947-2
Product certifications	ASEFA
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes