



Main

| | |
|-------------------------------------|---------------------------------|
| Range | Acti9 |
| Product or component type | Add-on residual current devices |
| Device short name | Vigi iC40 |
| Range compatibility | Acti9 iC40 |
| Poles description | 1P + N |
| Neutral position | Left |
| [In] rated current | 25 A |
| Network type | AC |
| Earth-leakage sensitivity | 30 mA |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type A-SI (Super Immunised) |
| Product certifications | CE |
| Quality labels | OVE IMQ |

Complementary

| | |
|--|---|
| Device location in system | Outgoer |
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 230 V AC 50/60 Hz |
| Residual current tripping technology | Voltage independent |
| [Ui] rated insulation voltage | 400 V AC 50/60 Hz conforming to EN/IEC 61009-2-1 |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to EN/IEC 61009-2-1 |
| Local signalling | Fault indication |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| Electrical connection to mcb | By screws |
| 9 mm pitches | 2 |
| Height | 95 mm |
| Width | 36 mm |
| Depth | 74 mm |
| Net weight | 90 g |
| Colour | White |
| Mechanical durability | 20000 cycles |
| Electrical durability | 10000 cycles |
| Connections - terminals | Tunnel type terminal bottom 1...16 mm ² rigid Tunnel type terminal bottom 1...10 mm ² flexible |
| Wire stripping length | 14 mm for bottom connection |
| Tightening torque | 2 N.m bottom |

Environment

| | |
|---------------------------------------|--|
| Standards | EN/IEC 61009-2-1 |
| IP degree of protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree | 3 conforming to EN/IEC 61009-2-1 |
| Relative humidity | 95 % at 55 °C |
| Operating altitude | 2000 m |
| Ambient air temperature for operation | -25...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 118 g |
| Package 1 Height | 8.8 cm |
| Package 1 width | 11.3 cm |
| Package 1 Length | 4.4 cm |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free plastic parts & cables product |