

# Product data sheet

## Characteristics

# LV429215

Earth-leakage add-on protection module,  
ComPact NSX 100/160, MH type, 440 VAC to  
550 VAC, 30 mA to 10 A, 3 poles



### Main

Range of product	ComPact NSX100...250
Range	ComPact
Product or component type	Vigi add-on
Device application	Wiring
Range compatibility	ComPact NSX100 circuit breaker ComPact NSX160 circuit breaker
Poles description	3P
[In] rated current	160 A 100 A
Earth-leakage add-on module name	MH
Earth-leakage protection class	Class A
Residual earth-leakage sensitivity adjustment type	Adjustable 5 settings
Earth-leakage sensitivity	0.03 A 0.3 A 1 A 3 A 10 A
Residual earth-leakage time delay adjustment type	Adjustable 4 settings
[At] residual earth-leakage time delay adjustment	310 Ms 150 Ms 0 Ms 60 ms

### Complementary

Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	440...550 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	800 ms
Oversupply category	Class II

### Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.066 kg
Package 1 Height	14 cm
Package 1 width	14.4 cm
Package 1 Length	17 cm
Unit Type of Package 2	S04

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Number of Units in Package 2	12
Package 2 Weight	13.558 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

### Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------