

Main

| | |
|---------------------------|--|
| Device short name | CT module and voltage output |
| Product or component type | Current transformer |
| Device application | Control |
| Range compatibility | ComPact NSX100 ComPact NSX160 ComPact NSX250 |
| Poles description | 3P |
| [In] rated current | 125 A |
| Current transformer ratio | 125/5 A |
| Power consumption in VA | 1.1 VA |
| Accuracy class | Class 1 |

Complementary

| | |
|--------------------------------|-------------------------------------|
| [Ue] rated operational voltage | 530 V |
| Network type | AC |
| Network frequency | 50...60 Hz |
| Auxiliary connection terminal | Cable connector 2.5 mm ² |



Environment

| | |
|-----------------------------------|------------------------------|
| Electrical shock protection class | Class II |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK04 conforming to IEC 62262 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 968 g |
| Package 1 Height | 13.5 cm |
| Package 1 width | 14.3 cm |
| Package 1 Length | 17.3 cm |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 4 |
| Package 2 Weight | 4.346 kg |
| Package 2 Height | 30 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |

| | |
|--------------------------|---|
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|